

## Technical Data Sheet MS8221B

Manual Range Multimeter Middle Size

DK	BITAL MU			
H	2	ST	MS8221E	3
Ω 20	2M 20		200m 200m 200m 200m 200m 200m 200m 200m	
20k 2k 200			200 60 • 6	0
200µ <sup>●</sup> 2m <sup>●</sup> A 20r	200m		•20 •20 •2 V-	0
10A	20 ~/	0m 20m 2 A 10A	m hFE	
0	MAX 10A FUSED MAX 15 sr every 10 m		MAX 200mA FUSED	



## Application

MS8221 Series are portable professional measuring instruments with a large LCD display for easy reading. Single operation of a transform switch makes measurement convenient. Overload protection and low battery indication are provided, this meter is ideal for use in the fields, workshop, school, hobby and home applications.

Product Features			
Max. Display	1999		
Data Hold	$\checkmark$		
Diode Test	$\checkmark$		
Continuity Buzzer	$\checkmark$		
Polarity	$\checkmark$		
Auto Power Off	$\checkmark$		
Fuse	$\checkmark$		
Low Battery	$\checkmark$		
Battery Test	$\checkmark$		
Power	Battery 9V 6F22 X 1		
Size	158x74x31mm (6.22x2.91x1.22 inch)		
Weight	~220g (7.76 Ounces)(including battery)		

<b>Product Specifications</b>	Range	MS8221B
DC Voltage	200mV/2V/20V/200V/600V	±0.5%
AC Voltage	2V/20V/200V/600V	±0.8%
DC Current	200µA/2mA/20mA/200mA/10A	±0.8%
AC Current	2mA/20mA/200mA/10A	±1.2%
Resistance	$200\Omega/2K\Omega/20K\Omega/200K\Omega/2M\Omega/20M\Omega$	±0.8%
hFE	-	YES



Sifam Tinsley Instrumentation Ltd 1 Warner Drive, Springwood Industrial Estate, Braintree, Essex CM7 2YW Contact No. : +44 (0) 1376 335271 Email: sales@sifamtinsley.com www.sifamtinsley.co.uk